

- 8 -

CLAIMS:

1. A improved universal stand includes standard T-shaped base; two vertical support members one of which fixed on said base and stationary and another fixed on the foot and movable by said foot along the length of the leg of said base; two horizontal support members, each of said horizontal support members fixed on the top of
5 respective vertical support member, said horizontal support members being the tubes, two rotatable adjustable arms having a plurality of holes defined in parallel circles along the length of each of said arms, each of said arms placed into respective horizontal support member; a pair of carrying plates; adjustable handles, each handle
10 having an elongated slot to be adjustably attached on the respective plate, characterized by:
a carrier means, and
a crib.
- 15 2. The improved universal stand of claim 1 wherein said carrier means includes two pairs of bolts, each of said pairs of bolts being fixed on a respective rotatable adjustable arm next to the first end of each said arm in such a way that lengthwise axes of each pair of bolts and of said respective arm are parallel.
- 20 3. The improved universal stand of claim 2 wherein carrier means includes a pair of adjustable connecting means, each of adjustable connecting means includes preferably an elongated slot established along the length thereof to adjustably receive corresponding bolts fixed on respective arm, each of adjustable connecting means having first end free and second end fixed on the one side of said respective carrying
25 plate.
4. The improved universal stand of claim 3 wherein each of said carrying plates includes preferably a plurality of holes in the lower part thereof and wherein each of the carrying plates further includes preferably a slot along the length of the upper
30 part thereof.

- 9 -

5. The improved universal stand of claim 4 wherein said carrier means includes a bar means, said bar means having preferably two elongated slots established along the length thereof to be adjustably coupled onto said carrying plates.

5 6. The improved universal stand of claim 5 wherein carrier means includes at least one handle, said handle having a tube fixed on one end thereof, said tube being extended from one edge of handle for the thickness of the bar, said handle being adjustably coupled onto said bar means by corresponding bolt.

10 7. The improved universal stand of claim 1 wherein said crib includes a pair of L-shaped bar members, each of said L-shaped bar members includes preferably a plurality of holes defined in vertical part thereof to adjustably be engaged with the respective pair of said bolts fixed on the respective arm, each L-shaped bar member includes preferably a plurality of holes defined in the horizontal part thereof.

15

8. The improved universal stand of claim 7 wherein said crib includes at least two pairs of bolts, each of said bolts having an upper end and a lower end, said upper end of each bolt being adjustably engaged with the corresponding hole defined in the horizontal part of the respective L-shaped bar means.

20

9. The improved universal stand of claim 8 wherein said crib includes at least two pairs of frames, each upper side of said frames firmly coupled with lower end of corresponding long bolt.

25 10. The improved universal stand of claim 9 wherein said crib includes at least a pair of supports, each of said supports threaded freely through two opposite frames to relate to said pair of L-shaped bar means.